DRAFT FOR CONSULTATION

Land Transport Rule

Traffic Control Devices (Bilingual Signs) Amendment 2023

Draft for Consultation

Land Transport Rules are law produced by Waka Kotahi NZ Transport Agency for the Minister of Transport. This is the public consultation draft of Land Transport Rule: Traffic Control Devices (Bilingual Signs) Amendment 2023.

If you wish to comment on this draft Rule, please see the information about making a submission in the accompanying explanatory material. The deadline for submissions is 5pm Friday 30 June 2023.

Traffic Control Devices (Bilingual Signs) Amendment 2023

Contents

Section 1	Preliminary provisions	1
1.1	Title	1
1.2	Commencement	1
1.3	Principal Rule amended	1
1.4	Objective of Rule	1
Section 2	Amendments to Principal Rule	1
2.1	Clause 4.4 amended	1
2.2	Clause 4.4(9) amended (Installation of traffic signs)	2
2.3	Part 2 amended (Definitions)	2
2.4	Schedule 1 amended (Signs)	2
Schedule	Amendments to Schedule 1 of Land Transport Rule: Traffic	
Control D	Devices 2004	8

Section 1 Preliminary provisions

1.1 Title

This Rule is Land Transport Rule: Traffic Control Devices (Bilingual Signs) Amendment 2023.

1.2 Commencement

This Rule comes into force on [date to be confirmed].

1.3 Principal Rule amended

This Rule amends Land Transport Rule: Traffic Control Devices 2004.

1.4 Objective of Rule

The objective of this Rule is to amend *Land Transport Rule: Traffic Control Devices 2004* to—

- (a) create new traffic signs that convey messages in both te reo Māori and the English language; and
- (b) change some traffic signs that previously prescribed specific English words on a sign, to prescribe words that convey the message in both te reo Māori and the English language; and
- (c) to prescribe different formatting requirements that must be used when using both te reo Māori and English on the same sign (or on dual signs); and
- (d) to make other minor amendments (including making changes to size and colour, enabling symbols to be used on certain signs, and adding the Te Rā Aro ki a Matariki/Matariki Observance Day to the definition of public holiday).

Section 2 Amendments to Principal Rule

2.1 Clause 4.4 amended

2.1(1) After clause 4.4(3), insert:

4.4 (3A) More than one language may only be used on a traffic sign if explicitly provided for in Schedule 1, and the traffic sign complies with the details of that sign.

2.2 Clause 4.4(9) amended (Installation of traffic signs)

2.2(1) In clause 4.4(9)(b), after "any enactment", insert "(including, to provide greater clarity, Schedule 1)".

2.3 Part 2 amended (Definitions)

2.3(1) In Part 2, insert the following definition in the appropriate alphabetical order:

Official geographic name has the same meaning as in section 4 of the New Zealand Geographic Board (Ngā Pou Taunaha o Aotearoa) Act 2008.

2.3(2) In Part 2, replace the definition of "Public holiday" with:

Public holiday has the same meaning as provided in <u>clause</u> 1.6 of the *Land Transport (Road User) Rule 2004*.

- 2.3(3) In Part 2, in paragraph (b) of the definition of "School bus", replace (iii) with:
 - (iii) is not disapplying a sign indicating it is a school bus.

2.4 Schedule 1 amended (Signs)

- 2.4(1) In Schedule 1, under the heading 'Signs', above the last bullet point ("A traffic control device that conforms substantially with the form of a traffic control device prescribed in this Schedule is deemed to be an authorised traffic control device"), insert the following bullet points:
 - If an official geographic name exists, then the name used on a sign (such as a destination, location or place name) must comply with the *New Zealand Geographic Board (Ngā Pou Taunaha o Aotearoa) Act 2008*. If the official geographic name is a dual name, the dual name should be treated as one language only for the purpose of this rule.

For example, if the location is for the official geographic name 'Aoraki / Mount Cook' for an A15-1 sign, the specifications that apply are as per "Language, option B - If using one language only for the name of the locality".

• For letters 'a', 'e', 'o', or 'u' the formula for producing the macron is:

- 0.5 x capital letter* height = length of macron
- 0.5 x stroke width of capital letter* = thickness of macron
- 1.5 x width of macron = space between top of letter and macron.
- For letter 'i', the formula for producing the macron is:
 - o 0.33 x capital letter* height = length of macron
 - 0.5 x stroke width of capital letter* = width of macron
 - 1.5 x width of macron = space between top of letter and macron.

*Note: always apply the calculation as if the letter to which the macron applies is capitalised, regardless of whether the macron is being used on a capitalised or lower-case letter.

2.4(2) In Schedule 1, item relating to 'R6-2B Text or symbols that may appear below or beside Symbol R6-1B' replace the table relating to 'Bus stop' with the following table:

Bus stop

A stop for buses to allow the loading or unloading of passengers or at a terminus or stage point of a bus route and the driver must stay with the vehicle.

Legend	Description	Colour	Dimensions
	'[bus symbol]'	red (R)	symbol see R6-2S
	'Tūnga Pahi'	black	NZ Tpt Med 'x' height 27.5mm
	'Bus Stop'	red (R)	NZ Tpt Med 'x' height 27.5 mm

2.4(3) In Schedule 1, item relating to 'R6-2B Text or symbols that may appear below or beside Symbol R6-1B' replace the table relating to 'Coach stop' with the following table:

Coach stop

A stop for coaches to allow the loading or unloading of passengers. Parking of the coach is not permitted and while the coach is stopped the driver must stay with the vehicle.

Legend	Description	Colour	Dimensions
	'[bus symbol]'	red (R)	symbol see R6-2S
	'Tūnga Pahi'	black	NZ Tpt Med 'x' height 27.5mm
	'Coach Stop'	red (R)	NZ Tpt Med 'x' height 27.5 mm

- 2.4(4) In Schedule 1, revoke the following items:
 - (a) 'A11-5 Cycle route direction':
 - (b) 'A13-1.2 Intersection direction cycle route arrow board':
 - (c) 'A13-3.2 Intersection direction cycle route arrow board two directions':
 - (d) 'A15-2 Confirmation direction cycle route'.
- 2.4(5) In Schedule 1, replace the following items with the items set out in Part 1 of the Schedule of this Rule in their appropriate alphanumerical order:
 - (a) 'R1-5.1 Urban/urban threshold':
 - (b) 'R1-5.2 Rural threshold':
 - (c) 'R1-5.3 Motorway ends threshold':
 - (d) 'R1-5.4 Motorway begins threshold':
 - (e) 'R1-5.5 Safer Speed Area Threshold':
 - (f) 'R1-6.1 Kura School static variable speed limit':
 - (g) 'R1-8 Temporary speed limit':
 - (h) 'R1-8.1 Temporary speed limit':
 - (i) 'R1-8.3 Temporary speed limit for Unsafe Structure':
 - (i) 'R4-7 Bus lane':
 - (k) 'R4-7.1 Bus only':
 - (l) 'R4-7.2 Bus Lane or Bus Only single period':
 - (m) 'R4-7.3 Bus Lane or Bus Only two periods':
 - (n) 'R4-9 Cycle lane':
 - (o) 'R4-9.1 Cycle only':
 - (p) 'R5-11 No camping':
 - (q) 'W1-1.2 Road works supplementary new seal':

- (r) 'W1-1.3 Road works supplementary mobile machinery (1-line)':
- (s) 'W1-1.9 Road works supplementary works end':
- (t) 'W1-1.13 Road works supplementary bridge repairs':
- (u) 'W1-4 Road works supplementary temporary speed limit ahead':
- (v) 'W2-1.1 Hazard warning supplementary flooding':
- (w) 'W2-1.2 Hazard warning supplementary washout':
- (x) 'W2-1.3 Hazard warning supplementary line crew':
- (y) 'W2-1.5 Hazard warning supplementary tree felling':
- (z) 'W2-1.6 Hazard warning supplementary trucks crossing':
- (aa) 'W2-1.7 Hazard warning supplementary logging trucks':
- (bb) 'W2-1.8 Hazard warning supplementary no road marking':
- (cc) 'W2-1.9 Hazard warning supplementary signals changed':
- (dd) 'W2-1.10 Hazard warning supplementary signals not working':
- (ee) 'W2-1.11 Hazard warning supplementary new road layout':
- (ff) 'W2-1.13 Hazard warning supplementary cycle race':
- (gg) 'W2-1.14 Hazard warning supplementary runners':
- (hh) 'W2-1.15 Hazard warning supplementary walkers':
- (ii) 'W2-1.16 Hazard warning supplementary cyclists ahead':
- (jj) 'W2-1.17 Hazard warning supplementary runners ahead':
- (kk) 'W2-1.18 Hazard warning supplementary walkers ahead':
- (ll) 'W2-1.20 Hazard warning supplementary fire':
- (mm) 'W2-1.21 Hazard warning supplementary funeral':
- (nn) 'W2-1.23 Hazard warning supplementary hidden queue':
- (oo) 'W2-1.25 Hazard warning supplementary pedestrians':

```
(pp) 'W3-2.1 Slippery surface supplementary – ice/grit':
```

- (qq) 'W3-2.2 Slippery surface supplementary slow when wet':
- (rr) 'W3-3.1 Gravel surface supplementary new seal':
- (ss) 'W3-3.2 Gravel surface supplementary seal repairs':
- (tt) 'W3-6.1 Supplementary please stop on request':
- (uu) 'W3-7 Site access distance ahead':
- (vv) 'W3-8 Site access':
- (ww) 'W4-7.1 One lane supplementary sign':
- (xx) 'W5-1 Road closed ahead':
- (yy) 'W5-2 Detour ahead follow 'symbol':
- (zz) 'W5-4 Detour ends':
- (aaa) 'W6-6 Breakdown':
- (bbb) 'W7-2 Vehicle mounted sign road work':
- (ccc) 'W7-7 Thank you':
- (ddd) 'W7-7.1 Works end thank you':
- (eee) 'W11-3.2 Intersection sign supplementary concealed':
- (fff) 'W16-5.2 Kindergarten':
- (ggg) 'W16-5.3 Aged':
- (hhh) 'W17-1.1 School bus 'school bus':
- (iii) 'W17-1.2 School bus 'school':
- (jjj) 'A11-1 Advance direction word message':
- (kkk) 'A11-2 Advance direction multiple locality':
- (lll) 'A11-3 Advance direction stack':
- (mmm) 'A11-4 Advance direction map':
- (nnn) 'A12-1 Advance lane designation word message':
- (000) 'A12-2 Advance lane designation overhead':
- (ppp) 'A12-3 EXIT ONLY supplementary':
- (qqq) 'A13-1 Intersection direction arrow board':
- (rrr) 'A13-1.1 Intersection direction arrow board with distance':
- (sss) 'A13-2 Intersection direction arrow':

- (ttt) 'A13-3 Intersection direction arrow board two directions':
- (uuu) 'A15-1 Confirmation direction':
- (vvv) 'A17-1 Place name':
- (www) 'A40-7 Shared zone':
- (xxx) 'A41-1 Motorway':
- (yyy) 'A41-1.1 Motorway begins':
- (zzz) 'A41-1.2 Motorway ends advance information':
- (aaaa) 'A41-1.3 Motorway ends':
- (bbbb) 'A41-2 Expressway':
- (cccc) 'A41-2.1 Expressway begins':
- (dddd) 'A41-2.2 Expressway ends advance information':
- (eeee) 'A41-2.3 Expressway ends':
- (ffff) 'A51-1 Cycle route advance direction primary route':
- (gggg) 'A51-2 Cycle route advance direction map primary route':
- (hhhh) 'A51-3 Cycle route intersection direction primary route':
- (iiii) 'A51-4 Cycle route intersection direction arrow local route':
- (jjjj) 'A51-5 Cycle route direction primary route':
- (kkkk) 'A51-8 Cycle route confirmation direction primary route'.
- 2.4(6) In Schedule 1, insert the items set out in Part 2 of the Schedule in this Rule in their appropriate alphanumerical order.

Schedule

Amendments to Schedule 1 of Land Transport Rule: Traffic Control Devices 2004

Part 1 Items replaced in Schedule 1 of Land Transport Rule: Traffic Control Devices 2004

Ref: clause 2.5(5)(a)

			Ref. Clause 2.3(3)(a)
R1-5.1	Urban threshold		
Highest speed limit reached.	t is the number of km/h shown on the s	ign; combined with	n name of locality
Shape and size	rectangle 900 x 1200 mm		
Background	green (R) or blue (R)		
Border	white (R) 30 mm		
Legend	Description	Colour	Size
	R1-1 with surrounding halo,	R1-1: black, red (R) and white (R), surrounding halo: white (R)	as for R1-1, surrounding halo: 20 mm
	above,		
Language, option A	If using both te reo Māori and English names for the same locality:		
	'[te reo Māori name of locality]' (sentence case), above	yellow (R)	75/15
	'[English name of locality]' (sentence case)	white (R)	75/15
	or		
Language, option			
В	If using one language only for the name of the locality:		
	'[locality]' (sentence case)	white (R)	75/15

Ref: clause 2.4(5)(b)

R1-5.2 Rural threshold

Highest speed limit is the number of km/h shown on the sign; combined with name of locality reached. Two options.

 $Option\ A$

Shape and size rectangle 1900 x 3000 mm

Background green (R) or blue (R)

Border	white (R) 60 mm		
Legend	Description	Colour	Size
	R1-1 with surrounding halo, above	R1-1: black, red (R) and white (R), surrounding halo: white (R)	as for R1-1: 1200 mm diameter, surrounding halo: 40 mm
Language, option A	If using both te reo Māori and English names for the same locality:		
	'Haere Mai Ki' or 'Nau Mai Ki' above	yellow (R)	100/20
	'[te reo Māori name of locality]' (sentence case), above	yellow (R)	160/32
	'Welcome to', above	white (R)	100/20
	'[English name of locality]' (sentence case)	white (R)	160/32
Language, option			
В	If using one language only for the name of the locality:		
	'Haere Mai Ki' or 'Nau Mai Ki' above	yellow (R)	100/20
	'Welcome to' above	white (R)	100/20
	'[locality]' (sentence case)	white (R)	160/32

Option B

Note: option B includes a different sign on each side of the road. If using both te reo Māori and English names for the same locality, the te reo Māori name of the locality must be on the sign for the left side of the road, while the English name for the locality must be on the sign for the right side of the road. If just using one language only for the name of the locality, then the same language will be on both signs.

Sign for the left side of the road

Shape and size	rectangle 1800 x 2550 mm		
Background	green (R) or blue (R)		
Border	white (R) 50 mm		
Legend	Description	Colour	Size
	R1-1 with surrounding halo, above	R1-1: black, red (R) and white (R) surrounding halo: white (R)	as for R1-1; 1200 mm diameter, surrounding halo: 40 mm
Language, option	'HAERE MAI' above	white (R)	100/15.5
A	'KI'	white (R)	100/15.5
	or		

Language, option B	'NAU MAI' above "KI'	white (R) white (R)	100/15.5 100/15.5
	Language option A or B above,		
	'[locality]' (sentence case)	white (R)	160/32

Sign for the right side of the road

Shape and size	rectangle 1800 x 2550 mm		
Background	green (R) or blue (R)		
Border	white (R) 50 mm		
Legend	Description	Colour	Size
	R1-1 with surrounding halo, above,	R1-1: black, red (R) and white (R), surrounding halo: white (R)	R1-1 as for R1-1: 1200 mm diameter, surrounding halo: 40 mm
	'WELCOME' above	white (R)	100/15.5
	'TO', above	white (R)	100/15.5
	'[locality]' (sentence case)	white (R)	160/32

Ref: clause 2.4(5)(c) R1-5.3 Motorway ends threshold

Highest speed limit is the number of km/h shown on the sign and advises the motorway, with the special road rules that apply, ends.

Shape and size	rectangle 1350 x 1650 mm		
Background	green (R)		
Border	white (R) 30 mm		
Legend	Description	Colour	Size
	R1-1 with surrounding halo	R1-1: black, red (R) and white (R), surrounding halo: white (R)	as for R1-1, surrounding halo: 20 mm
	above		
	'KUA MUTU'	white (R)	120/18.7
	'TE ARA'	white (R)	120/18.7
	'WHĀNUI'	white (R)	120/18.7
	'MOTORWAY'	white (R)	120/16.8

white (R)

120/16.8

'ENDS'

Ref: clause 2.4(5)(d)

K1-5.4 Motorway begins thresho	R1-5.4	Motorway begins threshold
--------------------------------	--------	---------------------------

Highest speed limit is the number of km/h shown on the sign, advises the named motorway begins and informs that pedestrians and cycles are not permitted beyond the sign.			
Shape and size	rectangle minimum 1050 mm width may be increased to suit motorway name x 2200 mm		
Background	green (R)		
Border	white (R) 40 mm		
Legend	Description	Colour	Size
	as for R1-1 with surrounding halo	R1-1: black, red (R) and white (R), surrounding halo: white (R)	as for R1-1, surrounding halo: 25 mm
	above		
	'TE ARA'	white (R)	120/18.7
	'WHĀNUI O'	white (R)	120/18.7
	'[motorway name]' above	white (R)	120/18.7
	'[motorway name]' above	white (R)	120/16.8
	'MOTORWAY' above	white (R)	120/16.8
	R5-2 'no pedestrian' beside	black, red (R) and white (R)	as for R5-2

Ref: clause 2.4(5)(e)

as for R5-1

R1-5.5 Safer Speed Area Threshold

R5-1 'no cycling'

The speed limit shown on the sign has been set in accordance with Safe System principles and applies to the roads in the area beyond the sign.

black, red (R)

and white (R)

Shape and size	rectangle:
	1200 x 1650 mm (approach speed < 60 km/h)
	1200 x 2100 mm (approach speed 60 - 80 km/h)
	1800 x 2550 mm (approach speed > 80 km/h)
Background	blue (R) or green (R)
Border	white (R):
	1200 x 1650 mm sign size 30 mm
	1200 x 2100 mm sign size 40 mm
	1800 x 2550 mm sign size 50 mm

Legend	Description	Colour	Size
	R1-1 with surrounding halo	R1-1: white	As for R1-1:
		(R), red (R) and black,	600 mm diameter (approach speed < 60 km/h)
		surrounding halo: white (R)	750 mm diameter (approach speed 60 - 80 km/h)
			900 mm diameter (approach speed > 80 km/h), surrounding halo
	above		20 mm (600 mm diameter)
			25 mm (750 mm diameter)
			30 mm (900 mm diameter)
	"Wāhi Pae" "Tere"	yellow (R)	100/20 (approach speed < 60 km/h)
	"Haumaru"		120/24 (approach speed 60 - 80 km/h)
			160/32 (approach speed > 80 km/h)
	"Safer Speed" "Area"	white (R)	100/20 (approach speed < 60 km/h)
	.1100		120/24 (approach speed 60 - 80 km/h)
			160/32 (approach speed > 80 km/h)

Ref: clause 2.4(5)(f)

R1-6.1 Kura School static variable speed limit

Highest speed limit is the number of km/h shown on the sign that applies to a road outside a school during the time specified. Must only be used on No exit or Give-way or Stop sign controlled side roads adjacent to a road outside a school signed by R1-6 signs.

Note: only a speed value of 60 or less that is appropriate to a road outside a school can be used with this sign.

Shape and size

rectangle backing board 980 x 1850 mm (white (R) background) incorporating: a 'School Days - static variable speed limit sign' (as specified below), above a 'Kura School – supplementary sign' (as specified below).

'School Days' – static variable speed limit sign				
Shape and Size	980 x 1850 mm			
Background	white (R)			
Border	red (R) 30 mm			
Legend	Description	Colour	Size	
	R1-1,	black, red (R) and white	as for R1-1	
	above			
	'[time of day that static variable speed limit applies]'	black	'[hours]' and '[minutes]' 80/12.4, 'AM' or 'PM' 60/9.6	
	for example,			
	'8:25-9:00 AM'	black	'[hours]' and '[minutes]' 80/12.4, 'AM' 60/9.6	
	'2:55-3:15 PM',	black	'[hours]' and '[minutes]' 80/12.4, 'PM' 60/9.6	
	'I NGĀ RĀ KURA'	black	80/13.8	
	'SCHOOL DAYS',	black	80/12.4	
ABOVE				
'Kura school' – su	pplementary sign			
Shape and size	rectangle 750 x 500 mm			
Background	yellow-green (RF)			
Border	black 20 mm			
Legend	Description	Colour	Size	
	'KURA'	black	125/21	
	'SCHOOL'	black	125/19.5	

Ref: clause 2.4(5)(g)

K1-8	Temporary speed	limit
	y y y y y y y	

 ${\it Highest speed limit is the number of km/h shown on the sign.}$

Shape and size R1-1, 600 mm diameter sign (background, border and legend as for R1-1)

above a 'Temporary' supplementary sign

'Temporary' supplementary sign

Shape and size rectangle 900 x 450 mm

Background	orange (RF)		
Border	black 25 mm		
Legend	Description	Colour	Size
	'Taupua'	black	Text: Tpt Med 'x' height 86 mm
	'TEMPORARY'	black	120/16.8

Ref: clause 2.4(5)(h)

R1-8.1 Temporary speed limit

Highest speed limit is the number of km/h shown on the sign.

Shape and size rectangle backing board, 1200 x 1500 mm (white background, black border,

legend as for R1-1 (900 mm diameter)) above a 'Temporary'

supplementary sign

'Temporary' supplementary sign

Shape and size rectangle 1650 x 750 mm

Background orange (RF)
Border black 30 mm

Legend Description Colour Size

'Taupua' black Text: Tpt Med 'x' height 125 mm

'TEMPORARY' black 175/24.5

Ref: clause 2.4(5)(i)

R1-8.3 Temporary speed limit for Unsafe Structure

Combination R1-1 speed limit sign above a W1-1.13 bridge repairs, road works supplementary – bridge repairs sign to advise that the speed limit displayed is a temporary speed limit due to an unsafe structure. Two options.

Option A

Shape and size R1-1 speed limit sign: circle 750 mm diameter above

W1-1.13 road works supplementary: rectangle 900 x 900 mm

Background R1-1 speed limit sign: white (R)

W1-1.13 road works supplementary – bridge repairs sign: orange (RF)

Border R1-1 speed limit sign: red (R) 95mm

W1-1.13 road works supplementary

sign: black 25mm

LegendDescriptionColourSizeR1-1'[speed limit in km/h]'black250/40above

	W1-1.13	As fo	or W1-1.13	As for W1-1.13
Option B				
Shape and size	R1-1 speed limit sign on rectangle b	acking ho	oard 1200 x 1	200 mm, above
Shape and size	W1-1.13 road works supplementary	_		
	1200 mm		F	
Background	backing boards: white (R)			
Border	black 30mm or may have no border			
Legend	Description		Colour	Size
	R1-1 speed limit sign on rectangle board 1200mm x 1200mm above	oacking	white (R), red (R) R1-1 speed limit sign above	900mm or 1200mm diameter
	W1-1.13 road works supplementary repairs sign	- bridge	orange (RF) and black, as for W1- 1.13	Rectangle 1200 x 600 mm
				Ref: clause 2.4(5)(j)
R4-7	Bus lane			
Adjacent lane is a	a bus lane available to buses, cycles, n	nopeds an	d motorcycle	es.
Shape and size	rectangle at least 600 x 800 mm			
Background	white (R)			
Border	red (R) 15 mm			
Legend	Description	Colou	r i	Size
	'symbol of bus (side-on)' above	black		465 x 160 mm
	'ARA'	black		120/18.7
	'LANE'	black		120/16.8
				Ref: clause 2.4(5)(k)
R4-7.1	Bus only			· · · · · · · · · · · · · · · · · · ·
Adjacent lane is a	available only to buses.			
Shape and size	rectangle at least 750 x 750 mm			
Background	white (R)			
Border	red (R) 15 mm			
Legend	Description	Colou	r i	Size

'symbol of bus (side-on)' above	black	465 x 160 mm	
'ANAKE'	black	120/18.7	
'ONLY'	black	120/16.8	

Ref: clause 2.4(5)(1)

'AM' or 'PM' 30/5.2

'[days]' 40/6.9

'[days]' 40/6.2

black

black

K4-7.2 Dus Lane of Dus Only – single period	R4-7.2	Bus Lane or Bus Only - single period
---	--------	--------------------------------------

Adjacent lane is a special vehicle lane available only to heavy motor vehicles. Two options.

Shape and size Background	rectangle 750 x height to fit text white (R)		
Border	red (R) 15 mm		
Option A			
Legend	Description 'symbol of bus (side-on)', above	Colour black	Size 465 x 160 mm
	'ARA'	black	120/18.7
	'LANE', above	black	120/16.8
	'[time period]', for example: 7.30 – 9.30 AM	black	'[hours]' 80/13.6, '[minutes]' 40/6.8, 'AM' or 'PM' 30/5.2
	'MANE – PARAIRE'	black	'[days]' 40/6.9
	'MON – FRI'	black	'[days]' 40/6.2
Option B			
Legend	Description	Colour	Size
	'symbol of bus (side-on)', above	black	465 x 160 mm
	'ANAKE'	black	120/18.7
	'ONLY', above	black	120/16.8
	'[time period]', for example: 7.30 – 9.30 AM	black	'[hours]' 80/13.6, '[minutes]' 40/6.8,

'MANE - PARAIRE'

`MON-FRI'

Ref: clause 2.4(5)(m)

Ref: clause 2.4(5)(n)

Adjacent lane is a special vehicle lane available only to heavy motor vehicles. Two options.

Shape and size rectangle 750 x height to fit text

Background white (R)

Border red (R) 15 mm

Option A

Legend	Description 'symbol of bus (side-on)', above	Colour black	Size 465 x 160 mm
	'ARA'	black	120/18.7
	'LANE', above	black	120/16.8
	'[time periods]', for example:	black	'[hours]' 80/13.6, '[minutes]' 40/6.8,
	7.30 – 9.30 AM		'AM' or 'PM' 30/5.2
	4.00 – 6.00 PM		
	'MANE – PARAIRE'	black	'[days]' 40/6.9
	'MON – FRI'	black	'[days]' 40/6.2
Option B			
Legend	Description	Colour	Size
Legend	Description 'symbol of bus (side-on)', above	Colour black	Size 465 x 160 mm
Legend	-		
Legend	'symbol of bus (side-on)', above	black	465 x 160 mm
Legend	'symbol of bus (side-on)', above 'ANAKE'	black	465 x 160 mm 120/18.7 120/16.8 '[hours]' 80/13.6,
Legend	'symbol of bus (side-on)', above 'ANAKE' 'ONLY', above	black black black	465 x 160 mm 120/18.7 120/16.8
Legend	'symbol of bus (side-on)', above 'ANAKE' 'ONLY', above '[time periods]', for example:	black black black	465 x 160 mm 120/18.7 120/16.8 '[hours]' 80/13.6, '[minutes]' 40/6.8, 'AM' or 'PM'
Legend	'symbol of bus (side-on)', above 'ANAKE' 'ONLY', above '[time periods]', for example: 7.30 – 9.30 AM	black black black	465 x 160 mm 120/18.7 120/16.8 '[hours]' 80/13.6, '[minutes]' 40/6.8, 'AM' or 'PM'
Legend	'symbol of bus (side-on)', above 'ANAKE' 'ONLY', above '[time periods]', for example: 7.30 – 9.30 AM 4.00 – 6.00 PM	black black black black	465 x 160 mm 120/18.7 120/16.8 '[hours]' 80/13.6, '[minutes]' 40/6.8, 'AM' or 'PM' 30/5.2

Cycle lane

R4-9

Adjacent lane is a	available to cycles.		
Shape and size	rectangle 600 x 750 mm		
Background	white (R)		
Border	red (R) 15 mm		
Legend	Description 'symbol of cycle' above	Colour black	Size 305 x 200 mm
	'ARA'	black	120/18.7
	'LANE'	black	120/16.8
			Ref: clause 2.4(5)(o)
R4-9.1	Cycle only		
Adjacent path is d	available only to cycles.		
Shape and size	rectangle at least 750 x 750 mm		
Background	white (R)		
Border	red (R) 15 mm		
Legend	Description	Colour	Size
	'symbol of cycle' above	black	305 x 200 mm
	'ANAKE'	black	120/18.7
	'ONLY'	black	120/16.8
R5-11	No camping		Ref: clause 2.4(5)(p)
	y time in the area designated by the s	rian	
No camping at av	iy iime in ine area aesignaiea by ine s	ngn.	
	rectangle 600 v 1000 mm		
Shape and size	rectangle 600 x 1000 mm		
	rectangle 600 x 1000 mm white (R) red (R) 30 mm		

Shape and size	rectangle 600 x 1000 mm		
Background	white (R)		
Border	red (R) 30 mm		
Legend	Description	Colour	Size
	'circle' with	red (R)	diameter 400 mm border 40 mm
	'diagonal bar' superimposed on	red (R)	bar 30 mm wide
	'symbol A20-S5' (symbol of tent above a caravan) above	black	240 x 300 mm
	'PUNINGA'	black	75/12
	'KORE'	black	75/12
	'NO'	black	75/11.5
	'CAMPING'	black	75/11.5

Ref: clause 2.4(5)(q)

W1-1.2	Road works supplementary – nev	v seal	
Newly laid road s	urface.		
Shape and size	rectangle 900 x 450 mm [suppleme	nts W1-1]	
Background	orange (RF)		
Border	black 25 mm		
Legend	Description	Colour	Size
	'Hīra Hou'	black	Text: Tpt Med 'x' height 86 mm
	'NEW SEAL'	black	120/18.7

			Ref: clause 2.4(5)(r)
W1-1.3	Road works supplementary – mobile machinery (1-line)		
A mobile machine	of the type named is operating beyond t	he sign.	
Shape and size	rectangle 900 x 650 mm [supplements W1-1]		
Background	orange (RF)		
Border	black 25 mm		
Legend	Description	Colour	Size
	'[te reo Māori name of the type of mobile machine]' (sentence case)	black	Text: Tpt Med 'x' height 86 mm
	'[English name of the type of mobile machine]' (upper case)	black	120/18.7
	For example:		
	'Pararahi'	black	Text: Tpt Med 'x' height 86 mm
	'GRADER'	black	120/18.7

Ref: clause 2.4(5)(s)

			Ref: clause 2.4(5)(s)
W1-1.9	Road works supplementary	– works end	
The area of road	work has ended.		
Shape and size	rectangle 1050 x 450 mm [sup	plements W1-1]	
Background	orange (RF)		
Border	black 30 mm		
Legend	Description	Colour	Size
	'Otinga Mahi'	black	Text: Tpt Med 'x' height 86 mm
	'WORKS END'	black	120/16.8

Ref: clause 2.4(5)(t)

W1-1.13	Road works supplementary – brid	dge repairs	
The bridge ahead	The bridge ahead is undergoing repairs.		
Shape and size	rectangle 900 x 900 mm [supplements W1-1]		
Background	orange (RF)		
Border	black 25 mm		
Legend	Description	Colour	Size
	'Whakatika'	black	Text: Tpt Med 'x' height 86 mm
	'Arawhiti'	black	Text: Tpt Med 'x' height 86 mm
	'BRIDGE'	black	120/18.7
	'REPAIRS'	black	120/18.7

Ref: clause 2.4(5)(u)

			Ref. Clause 2.4(3)(u)
W1-4	Road works supplementary – temp	porary speed limit	ahead
There are road wo	There are road works with a temporary speed limit ahead.		
Shape and size	rectangle 1450 x 750 mm [supplements W1-1B]		
Background	white (R)		
Border	black 30 mm		
Legend	Description	Colour	Size
	'[speed]' to the left of	black	numerals 300/48
	'km/h'	black	Tpt Med 'x' height 85 mm
	'KEI MUA'	black	120/20.6
	'AHEAD'	black	120/18.7

Ref: clause 2.4(5)(v)

W2-1.1	Hazard warning supplementary – flooding		
There is likely to be water across the road ahead.			
Shape and size rectangle 900 x 450 mm [supplements W2-1]			
Background	orange (RF)		
Border	black 25 mm		
Legend	Description	Colour	Size
	'Waipuke'	black	Text: Tpt Med 'x' height 86 mm

Text: Tpt Med 'x' height 86 mm

black

	'FLOODING'	black	120/18.7
11/2 1 2	П	4	Ref: clause 2.4(5)(w)
W2-1.2	Hazard warning supplem	ientary – washout	
·	thead has been washed out.		
Shape and size	rectangle 900 x 650 mm [s	upplements W2-1]	
Background	orange (RF)		
Border	black 25 mm		
Legend	Description	Colour	Size
	'Kua'	black	Text: Tpt Med 'x' height 86 mm
	'Horoa'	black	Text: Tpt Med 'x' height 86 mm
	'WASHOUT'	black	120/18.7
Line crew are wo Shape and size Background Border Legend	rking ahead. rectangle 1050 x 650 mm [source (RF) black 30 mm Description	supplements W2-1] Colour	Size
	'Ohu Mahi'	black	Text: Tpt Med 'x' height 86 mm
	'Hiko'	black	Text: Tpt Med 'x' height 86 mm
	'LINE CREW'	black	120/18.7
			Ref: clause 2.4(5)(y)
W2-1.5	Hazard warning supplem	entary – tree felling	
Trees are being for	elled beside the road.		
Shape and size	rectangle 900 x 900 mm [s	upplements W2-1]	
Background	orange (RF)		
Border	black 25 mm		
Legend	Description	Colour	Size

'Tope'

'Rākau'	black	Text: Tpt Med 'x' height 86 mm
'TREE'	black	120/18.7
'FELLING'	black	120/18.7

			Ref: clause 2.4(5)(z)
W2-1.6	Hazard warning supplementary –	trucks crossing	
Trucks are crossing	g where they do not normally or in gre	eater numbers.	
Shape and size	rectangle 900 x 900 mm [supplemen	ts W2-1]	
Background	orange (RF)		
Border	black 25 mm		
Legend	Description	Colour	Size
	'Whitinga'	black	Text: Tpt Med 'x' height 86 mm
	'Taraka'	black	Text: Tpt Med 'x' height 86 mm
	'TRUCKS'	black	120/18.7

Ref: clause 2.4(5)(aa)

120/18.7

W2-1.7 Hazard warning supplementary - logging trucks

Logging trucks are crossing where they do not normally or there are more of them on the road than usual.

black

Shape and size rectangle 900 x 900 mm [supplements W2-1]

'CROSSING'

Background orange (RF) Border black 25 mm

Legend	Description	Colour	Size
	'Taraka'	black	Text: Tpt Med 'x' height 86 mm
	'Tūporo'	black	Text: Tpt Med 'x' height 86 mm
	'LOGGING'	black	120/18.7
	'TRUCKS'	black	120/18.7

Ref: clause 2.4(5)(bb)

W2-1.8 Hazard warning supplementary – no road marking Road marking has been removed, obscured or is yet to be installed where it would be expected to be marked.

Shape and size rectangle 900 x 900 mm [supplements W2-1]

Background orange (RF)
Border black 25 mm

Legend **Description** Colour Size 'Rori Tohu' black Text: Tpt Med 'x' height 86 mm 'Kore' black Text: Tpt Med 'x' height 86 mm 'NO ROAD' black 120/18.7 'MARKING' black 120/18.7

Ref: clause 2.3(5)(cc)

W2-1.9 Hazard warning supplementary – signals changed

The traffic signals ahead have had the displays or sequence of displays changed.

Shape and size rectangle 900 x 900 mm [supplements W2-1]

Background orange (RF)
Border black 25 mm

Legend	Description	Colour	Size
	'Tohu'	black	Text: Tpt Med 'x' height 86 mm
	'Rerekē'	black	Text: Tpt Med 'x' height 86 mm
	'SIGNALS'	black	120/18.7
	'CHANGED'	black	120/18.7

Ref: clause 2.3(5)(dd)

W2-1.10 Hazard warning supplementary – signals not working

The traffic signals ahead are not operating.

Shape and size rectangle 1200 x 900 mm [supplements W2-1]

Backgroundorange (RF)Borderblack 25 mm

Legend Description Colour Size

'Tohu Mahi' black Text: Tpt Med 'x'

height 86 mm

'Kore'	black	Text: Tpt Med 'x' height 86 mm
'SIGNALS NOT'	black	120/18.7
'WORKING'	black	120/18.7

Ref: clause 2.4(5)(ee)

			Kei. Clause 2.4(3)(ee)
W2-1.11	Hazard warning supplementary – new road layout		
The road layout al	head has been changed recently.		
Shape and size	rectangle 900 x 900 mm [supplemen	ts W2-1]	
Background	orange (RF)		
Border	black 25 mm		
Legend	Description	Colour	Size
	'Takoto'	black	Text: Tpt Med 'x' height 86 mm
	'Rori Hōu'	black	Text: Tpt Med 'x' height 86 mm
	'NEW ROAD'	black	120/16.8

black

Ref: clause 2.4(5)(ff)

120/16.8

W2-1.13 Hazard warning supplem	nentary – cycle race
--------------------------------	----------------------

There is a cycle race ahead – expect cyclists.

'LAYOUT'

Shape and size rectangle 1050 x 650 mm [supplements W2-1]

Background orange (RF)
Border black 25 mm
Legend Description

Legend	Description	Colour	Size
	'Taetae'	black	Text: Tpt Med 'x' height 86 mm
	'Pahikara'	black	Text: Tpt Med 'x' height 86 mm
	'CYCLE RACE'	black	120/16.8

Ref: clause 2.4(5)(gg)

W2-1.14	Hazard warning supplementary – runner
---------	---------------------------------------

There is a running event ahead – expect runners.

Shape and size rectangle 900 x 450 mm [supplements W2-1]

Background orange (RF)

Border	black 25 mm		
Legend	Description	Colour	Size
	'Ope Oma'	black	Text: Tpt Med 'x' height 86 mm
	'RUNNERS'	black	120/18.7

Ref: clause 2.4(5)(hh)

			1C1. Clause 2.4(3)(1111)
W2-1.15	Hazard warning supplementary -	- walkers	
There is a walking	g event ahead – expect walkers.		
Shape and size	rectangle 900 x 450 mm [suppleme	nts W2-1]	
Background	orange (RF)		
Border	black 25 mm		
Legend	Description	Colour	Size
	'Ope Hīkoi'	black	Text: Tpt Med 'x' height 86 mm
	'WALKERS'	black	120/18.7

Ref: clause 2.4(5)(ii)

W2-1.16	Hazard warning supplementary – c	vclists ahead

There is a cycling event ahead – expect cyclists.

Shape and size rectangle 900 x 1050 mm [supplements W2-1]

Background orange (RF)
Border black 30 mm

Legend	Description	Colour	Size
	'Ope Eke'	black	Text: Tpt Med 'x' height 86 mm
	'Pahikara'	black	Text: Tpt Med 'x' height 86 mm
	'Kei Mua'	black	Text: Tpt Med 'x' height 86 mm
	'CYCLISTS'	black	120/18.7
	'AHEAD'	black	120/18.7

Ref: clause 2.4(5)(jj)

W2-1.17 Hazard warning supplementary – runners ahead

There is a running event ahead – expect runners.

Shape and size rectangle 900 x 900 mm [supplements W2-1]

Background	orange (RF)		
Border	black 25 mm		
Legend	Description	Colour	Size
	'Ope Oma'	black	Text: Tpt Med 'x' height 86 mm
	'Kei Mua'	black	Text: Tpt Med 'x' height 86 mm
	'RUNNERS'	black	120/18.7
	'AHEAD'	black	120/18.7

Ref: clause 2.4(5)(kk)

W2-1.18	Hazard warning supplementary – walkers ahead
There is a walking	event ahead – expect walkers.

Shape and size rectangle 900 x 900 mm [supplements W2-1]

Background orange (RF)
Border black 25 mm

Legend	Description	Colour	Size
	'Ope Hīkoi'	black	Text: Tpt Med 'x' height 86 mm
	'Kei Mua'	black	Text: Tpt Med 'x' height 86 mm
	'WALKERS'	black	120/18.7
	'AHEAD'	black	120/18.7

Ref: clause 2.4(5)(11)

W2-1.20	Hazard warning supplementary – fire		
There is a fire ahe	ad.		
Shape and size	rectangle 600 x 450 mm [supplem	ents W2-1]	
Background	orange (RF)		
Border	black 25 mm		
Legend	Description	Colour	Size
	'Ahi'	black	Text: Tpt Med 'x' height 86 mm
	'FIRE'	black	120/18.7

Ref: clause 2.4(5)(mm)

W2-1.21 Hazard warning supplementary - funeral

There is a funeral ahead – there could be a large number of slow-moving or parked cars and pedestrians.

Shape and size rectangle 1200 x 450 mm [supplements W2-1 (Option A or Option B)]

Background orange (RF)
Border black 25 mm

Legend Description Colour Size

'Tangihanga' or 'Hui Mate' black Text: Tpt Med

'x' height 86

mm

'FUNERAL' black 120/16.8

Ref: clause 2.4(5)(nn)

W2-1.23 Hazard warning supplementary – hidden queue

There is likely to be a queue ahead which may be obscured.

'Rārangi'

Shape and size rectangle 750 x 900 mm [supplements W2-1]

Background orange (RF)
Border black 25 mm

Legend Description Colour Size

black Text: Tpt Med

'x' height 86

mm

'Huna' black Text: Tpt Med

'x' height 86

mm

'HIDDEN' black 120/18.7

'QUEUE' black 120/18.7

Ref: clause 2.4(5)(00)

W2-1.25 Hazard warning supplementary – pedestrians

There are likely to be pedestrians on the road ahead.

Shape and size rectangle 1050×450 mm [supplements W2-1]

Background orange (RF)
Border black 25 mm

Legend Description Colour Size

'Hunga Hīkoi' black Text: Tpt Med

'x' height 86

mm

'PEDESTRIANS' black 100/14

Ref: clause 2.4(5)(pp)

W3-2.1 Slippery surface supplementary – ice/grit

Danger of skidding ahead due to ice or grit.

Shape and size rectangle 1500 x 450 mm [supplements W3-2]

Background orange (RF) **Border** black 30 mm

Legend Description Colour Size

'Haupapa / Pūriki' black Text: Tpt Med 'x'

height 86 mm

'ICE / GRIT' black 120/18.7

Ref: clause 2.4(5)(qq)

W3-2.2 Slippery surface supplementary – slow when wet

Warns road users to slow down to avoid the danger of skidding due to the wet road surface.

Shape and size rectangle 900 x 900 mm [supplements W3-2]

Background orange (RF)
Border black 25 mm

Legend **Description** Colour Size 'Āta Haere' black Text: Tpt Med 'x' height 86 mm Text: Tpt Med 'x' 'Inā Mākū' black height 86 mm 'SLOW' black 120/20.6 'WHEN WET' black 120/18.7

Ref: clause 2.4(5)(rr)

W3-3.1 Gravel surface supplementary – new seal

Loose stones or chips – new seal ahead.

Shape and size rectangle 900 x 450 mm [supplements W3-3]

Border orange (RF)
black 25 mm

Legend Description Colour Size

'Hīra Hou' black Text: Tpt Med 'x'

height 89.3 mm

'NEW SEAL' black 125/18

Ref: clause 2.4(5)(ss)

Loose stones or chips – patches of new seal ahead.

Shape and size rectangle 1050 x 900 mm [supplements W3-3]

Background orange (RF)
Border black 25 mm

Legend **Description** Colour Size 'Whakatika' black Text: Tpt Med 'x' height 86 mm 'Hīra' black Text: Tpt Med 'x' height 86 mm 'SEAL' black 120/18.7 'REPAIRS' 120/18.7

Ref: clause 2.4(5)(tt)

W3-6.1 Supplementary – please stop on request

Stop when requested to do so, may supplement a W6-2 or W2-1.12, and, where appropriate, may replace a W6-2.

Shape and size rectangle 1200 x 900 mm

Background orange (Rf)
Border black 25 mm

Legend	Description	Colour	Size
	'Kia Mau'	black	Text: Tpt Med 'x' height 86 mm
	'Inā Tonoa''	black	Text: Tpt Med 'x' height 86 mm
	'PLEASE STOP'	black	120/16.8
	'ON REQUEST'	black	120/16.8

Ref: clause 2.4(5)(uu)

W3-7 Site access distance ahead

Access to the work site is the specified distance and road side indicated.

Shape and size rectangle 1200 x 1350 mm

Border orange (Rf)
black 30 mm

Legend Description Colour Size

'Urunga'	black	Text: Tpt Med 'x' height 89.5 mm
'Rohe'	black	Text: Tpt Med 'x' height 89.5 mm
'Mahi'	black	Text: Tpt Med 'x' height 89.5 mm
'SITE'	black	125/19.5
'ACCESS'	black	125/19.5
'[distance] m' all beside	black	numerals 160/24.5, 'm' Tpt Med 'x' height 100 mm
'symbol indicating access location'	black	100 x 900 mm

			Ref: clause 2.4(5)(vv)
W3-8	Site access		
Sign indicating sit	e access location.		
Shape and size	rectangle 1200 x 1800 mm		
Background	orange (Rf)		
Border	black 30 mm		
Legend	Description	Colour	Size
	'Urunga'	black	Text: Tpt Med 'x' height 86 mm
	'Rohe'	black	Text: Tpt Med 'x' height 86 mm
	'Mahi'	black	Text: Tpt Med 'x' height 86 mm
	'SITE'	black	160/25
	'ACCESS'	black	160/25
	'arrow pointing to left or right'	black	shaft 100 mm

			Ref: clause 2.4(5)(ww)
W4-7.1	One lane – supplementary sign		
Warn road users	the road ahead narrows to one lane.		
Shape and size	rectangle 900 x 650 mm [Suppleme	ents W4-7 or W4	4-8]
Background	orange (Rf)		
Border	black 25 mm		
Legend	Description	Colour	Size
	'Kotahi'	black	Text: Tpt Med 'x' height 86 mm

'Te Ara'	black	Text: Tpt Med 'x' height 86 mm
'ONE LANE'	black	120/16.8

			Ref: clause $2.4(5)(xx)$
W5-1	Road closed ahead		
Road closed ahea	d.		
Shape and size	rectangle 1200 x 900 mm		
Background	orange (Rf)		
Border	black 30 mm		
Legend	Description	Colour	Size
	'Rori Kati'	black	Text: Tpt Med 'x' height 86 mm
	'Kei Mua'	black	Text: Tpt Med 'x' height 86 mm
	'ROAD CLOSED'	black	120/18.7
	'AHEAD'	black	120/18.7

Ref: clause 2.4(5)(yy)

W5-2	Detour ahead follow	'symbol'
------	---------------------	----------

 $Detour\ ahead-the\ alternative\ route\ is\ indicated\ by\ a\ symbol\ in\ form\ of\ W5-2.11,\ 2.12\ or\ 2.13.$

Shape and size rectangle 1350 x 900 mm

Background orange (Rf) black 30

Border	black 30 mm		
Legend	Description	Colour	Size
	'Autaki Kei Mua'	black	Text: Tpt Med 'x' height 86 mm
	'Whāia', beside	black	Text: Tpt Med 'x' height 71.4 mm
	'detour symbol, W5-2.11, 2.12 or 2.13'	black and white (R)	as for W5-2.11, 2.12 or 2.13
	'DETOUR AHEAD'	black	12/18.7
	'FOLLOW' beside	black	100/15.5
	'detour symbol, W5-2.11, 2.12 or 2.13'	black and white (R)	as for W5-2.11, 2.12 or 2.13

Ref: clause 2.4(5)(zz)

W5-4 **Detour ends**

Detour ends – normal route continues.

Shape and size rectangle 750 x 900 mm

Background orange (Rf)
Border black 25 mm

Legend Description Colour Size

'Otinga' black Text: Tpt Med

'x' height 86

mm

'Autaki' black Text: Tpt Med

'x' height 86

mm

'DETOUR' black 120/18.7

'ENDS' black 120/18.7

Ref: clause 2.4(5)(aaa)

W6-6 'Breakdown'

Breakdown ahead (for use by a worker involved in removing the temporary hazard caused by a breakdown).

Shape and size rectangle 900 x 650 mm

Background orange (Rf)
Border black 25 mm

Legend Description Colour Size

'Waka' black Text: Tpt Med 'x' height 86 mm

'Pakaru' black Text: Tpt Med 'x'

height 86 mm

'BREAKDOWN' black 120/16.8

Ref: clause 2.4(5)(bbb)

W7-2 Vehicle mounted sign – road work

The vehicle is involved with work on road – pass with care.

Shape and size rectangle 900 x 900 mm

Background orange (RF)
Border black 25 mm

Legend Description Colour Size

'Mahinga' black Text: Tpt Med 'x'

height 86 mm

'Rori'	black	Text: Tpt Med 'x' height 86 mm
'ROAD'	black	120/18.7
'WORK'	black	120/18.7

Ref: clause 2.4(5)(ccc)

W7-7	Thank you		
Thank you.			
Shape and size	rectangle 900 x 450 mm		
Background	orange (Rf)		
Border	black 25 mm		
Legend	Description	Colour	Size
	'Tēnā Koe'	black	Text: Tpt Med 'x' height 86 mm
	'THANK YOU'	black	120/16.8

Ref: clause 2.4(5)(ddd)

W7-7.1	Works end thank you	
The road works ho	ave ended.	
Shape and size	rectangle 1050 x 900 mm	
Background	orange (Rf)	
Border	black 25 mm	
Legend	Description	Colour
	'Otinga Mahi'	black

120/16.8 120/16.8

Text: Tpt Med 'x' height 86

Text: Tpt Med

'x' height 86

Size

mm

mm

black

black

black

Ref: clause 2.4(5)(eee)

W11-3.2	ntersection sign suppl	ementary – concealed
---------	------------------------	----------------------

'Tēnā Koe'

'WORKS END'

'THANK YOU'

The intersection ahead is concealed.

Shape and size rectangle 750 x 450 mm [supplements W11 series signs where appropriate]

Background yellow (R)
Border black 25 mm

Legend	Description	Colour	Size
	'HUNA'	black	100/15.5
	'CONCEALED'	black	100/14

Ref: clause 2.4(5)(fff)

W16-5.2	Kindergarten
---------	--------------

The pedestrians or crossing is associated with a kindergarten.

Shape and size rectangle 1200 x 450 mm [supplements W16-2 or W16-4]

Background yellow (R) or yellow-green (RF)

[same colour as the W16 sign supplemented]

Border black 30 mm

LegendDescriptionColourSize'KURA PŪHOU'black100/17'KINDERGARTEN'black100/15.5

Ref: clause 2.4(5)(ggg)

W16-5.3 Aged

The pedestrians are most likely to be older persons.

Shape and size rectangle 1200 x 400 mm [supplements W16-1]

Background yellow (R) or yellow-green (RF)

[same colour as the W16-1 sign supplemented]

Border black 30 mm

Legend Description Colour Size

'AHUNGARUA' or 'KAUMĀTUA'

'AGED' black 100/15.5

Ref: clause 2.4(5)(hhh)

W17-1.1 School bus - 'school bus'

Drivers must slow to 20 km/h if a bus has stopped to pick up or drop off children – clause 5.6 of Land Transport (Road User) Rule 2004.

Shape and size rectangle 1200 x 525 mm

Background yellow (F) or yellow-green (RF)

Border black 30 mm

Legend Description Colour Size

'PAHI KURA' black 150/23

'SCHOOL BUS'	black	150/21	

Ref: clause 2.4(5)(iii)

W17-1.2 School bus – 'school'

Drivers must slow to 20 km/h if a bus has stopped to pick up or drop off children – clause 5.6 of Land Transport (Road User) Rule 2004.

Shape and size rectangle 900 x 525 mm

Background yellow (F) or yellow-green (RF)

Border black 25 mm

Legend Description Colour Size

'KURA' black 150/23

'SCHOOL' black 150/21

Ref: clause 2.4(5)(jjj)

A11-1 Advance direction – word message

Advises road users direction to follow at intersection ahead to reach a specific locality.

Shape and size rectangle sized to suit message

Background green (R) or blue (R)

Border white (R) 40 mm

201401	(11) 10 IIIII		
Legend	Description	Colour	Size
	Optional A20-S11 (emergency medical services), above or beside the locality names	As for A20- S11	As for A20-S11
	Optional A20-S18 (airfield), above or beside the locality names	As for A20- S18	As for A20-S18
	Optional an A16 series route indicator symbol, above or beside the locality names, which may be:	As for A16	As for A16
Language, option A	If using both te reo Māori and English name for the locality:		
	'[te reo Māori name of locality]' (sentence case),	yellow (R)	120/24
	above a direction, which may be:		

Direction, option 1	'HURI MAUĪ'	yellow (R)	100/15.5
	or		
Direction, option 2	'HURI MATAU'	yellow (R)	100/15.5
	or		
Direction., option 3	'PUTANGA'	yellow (R)	100/15.5
	above,		
	'[English name of locality]' (sentence case),	white (R)	120/24
	above a direction, which may be:		
Direction, option 1	'TURN LEFT'	white (R)	100/15.5
	or		
Direction, option 2	'TURN RIGHT'	white (R)	100/15.5
	or		
Direction., option 3	'EXIT'	white (R)	100/15.5
	Direction to sit beside or above distance, which may be:		
Distance, option 1	'[distance] m'	white (R)	100/15.5 numerals Tpt Med 'x' = 65 letter
	or		
Distance, option 2	'[distance] km'	white (R)	100/15.5 numerals Tpt Med 'x' = 65 letter
Language, option B	If using one language only for the name of the locality:		
	'[locality]' (sentence case)	white (R)	120/24
	Above a direction, which may be:		

Direction, option 1	'HURI MAUĪ'	yellow (R)	100/15.5
	'TURN LEFT'	white (R)	100/15.5
	or		
Direction, option 2	'HURI MATAU'	yellow (R)	100/15.5
	'TURN RIGHT'	white (R)	100/15.5
	or		
Direction., option 3	'PUTANGA'	yellow (R)	100/15.5
	'EXIT'	white (R)	100/15.5
	Direction option 1, 2 or 3 beside or above distance, which may be:		
Distance, option 1	'[distance] m'	white (R)	100/15.5 numerals Tpt Med 'x' = 65 letter
	or		
Distance, option 2	'[distance] km'	white (R)	100/15.5 numerals Tpt Med 'x' = 65 letter

Ref: clause 2.4(5)(kkk)

A11-2 Advance direction – 2 localities

Advises road users direction to follow at intersection ahead to reach either of the two listed localities.

Shape and size	rectangle sized to suit message		
Background	green (R) or blue (R)		
Border	white (R) 40 mm		
Legend	Description	Colour	Size
	Optional A20-S11 (emergency medical services), above or beside the locality names	As for A20- S11	As for A20-S11

	Optional an A16 series route indicator symbol, above all locality names or beside the name of each locality	As for A16	As for A16
Language, option A	If using both te reo Māori and English names for locality 1:		
	'[te reo Māori name of locality 1]' (sentence case), above	yellow (R)	120/24
	'[English name of locality 1]' (sentence case),	white (R)	120/24
	or		
Language, option B	If using one language only for locality 1:		
	'[locality 1]' (sentence case),	white (R)	120/24
	Language option A or B beside:		
	'arrow (type D) aligned appropriately',	white (R)	shaft 70 mm
	above,		
Language, option A	If using both te reo Māori and English names for locality 2:		
	'[te reo Māori name of locality 2]' (sentence case), above	yellow (R)	120/24
	'[English name of locality 2]' (sentence case),	white (R)	120/24
	or		
Language, option B	If using one language only for locality 2:		
	'[locality 2]' (sentence case),	white (R)	120/24
	Language option A or B beside:		
	'arrow (type D) aligned appropriately'	white (R)	shaft 70 mm
NI 4	1	1 24 1	124

Notes: where road users would follow the same direction to reach either locality, a single arrow may be used.

Ref: clause 2.4(5)(111)

A11-3 Advance direction – stack

Advises road users direction to follow at intersection ahead to reach the localities described.

Shape and	rectangle sized to suit message		
size			
Background	green (R) or blue (R)		
Border	white (R) 40 mm		
Legend	Description	Colour	Size
	sign separated into 2 or 3 panels by lines	white (R)	25 mm
	Each panel contains:		
	Optional A20-S11 (emergency medical services), above or beside the locality names	As for A20- S11	As for A20-S11
	Optional A20-S18 (airfield), above or beside the locality names	As for A20- S18	As for A20-S18
	Optional, an A16 series route indicator symbol above all locality names in a given panel or beside name of each locality	As for A16	As for A16
Language, Option A	If using both te reo Māori and English names for locality:		
	'[te reo Māori name of locality]' (sentence case), above	yellow (R)	120/24
	'[English name of locality]' (sentence case)	white (R)	120/24
	or		
Language, Option B	If using one language only for locality:		
	'[locality]' (sentence case),	white (R)	120/24
	Language option A or B, beside:		
	'arrow (type D) aligned appropriately'	white (R)	shaft 70 mm

	Ref: clause 2.4(5)(mmm)
A11-4	Advance direction – map
Advises road us	sers direction to follow at intersection ahead to reach the localities described.
Shape and size	rectangle sized to suit message
Background	green (R) or blue (R)
Border	white (R) 50 mm

Legend	Description	Colour	Size
	Optional, A20-S11 (emergency medical services), above or beside the locality names	As for A20- S11	As for A20-S11
	Optional, A20-S18 (airfield), above or beside the locality names	As for A20- S18	As for A20-S18
	Optional, an A16 series route indicator symbol above or beside all locality names for a given direction on the map	As for A16	As for A16
	A symbolic map of the intersection depicted by lines which include a pointed end that illustrates a departure from the intersection, and	white (R)	120 mm line width
Language option A	If using both te reo Māori and English names for the locality:		
	'[te reo Māori name of locality]' (sentence case), above	yellow (R)	120/24
	'[English name of locality]' (sentence case)	white (R)	120/24
	or		
Language option B	If using one language only for the name of the locality:		
	'[locality]' (sentence case)	white (R)	120/24
	(repeat above as needed if multiple localities)		

Note: multiple locality names may be positioned relative to the map.

		I	Ref: clause 2.4(5)(nnn)
A12-1	Advance lane designation – word messag	ge	
Advises road us	ers which lane to enter at intersection ahead	l to reach the lo	ocalities described.
Shape and size	rectangle sized to suit message		
Background	green (R) or blue (R)		
Border	white (R) 40 mm		
Legend	Description	Colour	Size

	Optional, A20-S11 (emergency medical services), above or beside the locality names	As for A20- S11	As for A20-S11
	Optional, A20-S18 (airfield), above or beside the locality names	As for A20- S18	As for A20-S18
	Optional, an A16 series route indicator symbol, above all locality names in a given panel or beside the name of each locality	As for A16	As for A16
Language, option A	If using both te reo Māori and English names for the locality:		
	'[te reo Māori name of locality]' (sentence case),	yellow (R)	120/24
	above direction, which may be:		
Direction option A	'ARA MAUĪ'	yellow (R)	100/15.5
	or		
Direction option B	'ARA MATAU'	yellow (R)	100/15.5
	or		
Direction option C	'te reo Māori other descriptor of the lane', (upper case) above	yellow (R)	100/15.5
	'[English name of locality] (sentence case)	white (R)	120/24
	above direction, which may be:		
Direction option A	'LEFT LANE'	white (R)	100/15.5
	or		
Direction	'RIGHT LANE'	white (R)	100/15.5
option B	or		
Direction option C	'English other descriptor of the lane' (upper case)	white (R)	100/15.5
Language, option B	If using one language only for the name of the locality:		
	'[locality]' (sentence case),	white (R)	120/24
	above direction, which may be:		

'ARA MAUĪ', above	yellow (R)	100/15.5
'LEFT LANE'	white (R)	100/15.5
or		
'ARA MATAU', above	yellow (R)	100/15.5
'RIGHT LANE'	white (R)	100/15.5
or		
'te reo Māori other descriptor of the lane' (upper case), above	yellow (R)	100/15.5
'English other descriptor of the lane' (upper case)	white (R)	100/15.5
	'LEFT LANE' or 'ARA MATAU', above 'RIGHT LANE' or 'te reo Māori other descriptor of the lane' (upper case), above 'English other descriptor of the lane'	'LEFT LANE' white (R) or 'ARA MATAU', above yellow (R) 'RIGHT LANE' white (R) or 'te reo Māori other descriptor of the lane' (upper case), above 'English other descriptor of the lane' white (R)

Ref: clause 2.4(5)(000)

A12-2 Advance lane designation – overhead

Advises road users which lane or lanes to enter at intersection ahead to reach localities described. The arrow or arrows are erected directly over the lane to which they refer.

Shape and	rectangle sized to suit message
size	

Background green (R) or blue (R)

Border white (R) 40 mm

Legend	Description	Colour	Size
	Optional A20-S11 (emergency medical services), above or beside the locality names	As for A20- S11	As for A20-S11
	Optional A20-S18 (airfield), above or beside the locality names	As for A20- S18	As for A20-S18
	Optional, an A16 series route indicator symbol, above or beside name of locality	As for A16	As for A16
	Optional, an A16 series route indicator symbol, above or beside name of locality	As for A16	As for A16
Language, option A	If using both te reo Māori and English names for the locality:		
	'[te reo Māori name of locality]', (sentence case) above	yellow (R)	120/24

	(FE:==1:=1:£1===1:4=-1: (===4====	1-:4- (D)	120/24
	'[English name of locality]' (sentence	white (R)	120/24
	case)		
	or		
Language,	If using one language only for the name		
option B	of the locality:		
	'[locality]' (sentence case)	white (R)	120/24
	Language option A or B above,		
	'arrow (type D) or arrows aligned	white (R)	shaft 65 mm
	appropriately'		
	(repeat above as needed if multiple		
	localities)		

Notes: straight ahead is depicted by a downward-facing arrow. Multiple locality names may be positioned relative to the arrows.

Ref: clause 2.4(5)(ppp)

A12-3 EXIT ONLY supplementary

Advises road users the lane does not continue beyond the exit and they should move to an adjacent lane as soon as they may safely do so unless leaving the road by the exit indicated. Two options.

Shape and size	rectangle panel 700 mm high with width sized to suit the sign being supplemented
Background	yellow (R)
Border	white (R) 40 mm

Option A

Legend	Description	Colour	Size
	'PUTANGA ANAKE', above	black	200/34
	'EXIT ONLY'	black	200/31
	or		
Ontion P			

Option B

Legend	Description	Colour	Size
	'PUTANGA ANAKE', above	black	250/43
	'downward-facing arrow', between	black	shaft 65 mm
	'EXIT' and 'ONLY'	black	250/39

Ref: clause 2.4(5)(qqq)

A13-1 Intersection direction – arrow board

Advises road users direction to follow at intersection to reach a specific locality.

Shape and size

rectangle with a pointed end, height of 450 mm, and length to suit the message. Pointed end to point in the direction of the locality and be formed by an isosceles triangle, with its base being a vertical line equal to the height of the rectangle, and its height being a horizontal line approximately 40% of its base dimension

Background

green (R) or blue (R)

Border

white (R) 25 mm

Legend	Description	Colour	Size
	Optional A20-S11 (emergency medical services), above or beside the locality names	As for A20- S11	As for A20-S11
	Optional A20-S18 (airfield), above or beside the locality names	As for A20- S18	As for A20-S18
	Optional, an A16 series route indicator symbol beside the localities, above	As for A16	As for A16
Language, option A	If using both te reo Māori and English names for the locality:		
	'[te reo Māori name of locality]' (sentence case), above,	yellow (R)	160/32
	'[English name of locality]' (sentence case)	white (R)	160/32
	or		
Language, option B	If using one language only for the name of the locality:		
	'[locality]' (sentence case),	white (R)	160/32
	Language option A or B above,		
	a chevron parallel to, and located at the pointed end of the sign	white (R)	chevron 350 mm high, stripe width 130 mm.

Ref: clause 2.4(5)(rrr)

A13-1.1 Intersection direction – arrow board with distance

high, stripe width

130 mm.

Advises road users direction to follow at intersection to reach the localities described and the distance to each locality.

distance to each	h locality.		
Shape and size	rectangle with a pointed end, height of 450 mm, and length to suit the message. Pointed end to point in the direction of the locality and be formed by an isosceles triangle, with its base being a vertical line equal to the height of the rectangle, and its height being a horizontal line approximately 40% of its base dimension		
Background	green (R) or blue (R)		
Border	white (R) 25 mm		
Legend	Description	Colour	Size
	Optional A20-S11 (emergency medical services), above or beside the locality names	As for A20- S11	As for A20-S11
	Optional A20-S18 (airfield), above or beside the locality names	As for A20- S18	As for A20-S18
	Optional, an A16 series route indicator symbol may be included beside each locality name	As for A16	As for A16
Language, option A	If using both te reo Māori and English names for the locality:		
	'[te reo Māori name of locality]' (sentence case), above	yellow (R)	160/32
	'[English name of locality]' (sentence case),	white (R)	160/32
	or		
Language, option B	If using one language only for the name of the locality:		
	'[locality]' (sentence case),	white (R)	160/32
	Language option A or B beside,		
	'[distance] km'	white (R)	160/32 numerals Tpt Med 'x' = 80 letters
	a chevron parallel to, and located at the	white (R)	chevron 350 mm

pointed end of the sign,

localities)

(repeat above as needed if multiple

Ref: clause 2.4(5)(sss)

A13-2 Intersection direction – arrow

Advises road users direction to follow at an intersection to reach the localities described. Used where the road is not approximately at right angles to the approaching driver.

Shape and size	rectangle sized to suit message		
Background	green (R) or blue (R)		
Border	white (R) 25 mm		
Legend	Description	Colour	Size
	Optional, A20-S11 (emergency medical services), above or beside the locality names	As for A20- S11	As for A20-S11
	Optional, A20-S18 (airfield), above or beside the locality names	As for A20- S18	As for A20-S18
	Optional, an A16 series route indicator symbol may be included above or beside the list of localities	As for A16	As for A16
Language, option A	If using both te reo Māori and English names for the locality:		
	'[te reo Māori name of locality]' (sentence case), above	yellow (R)	160/32
	'[English name of locality]' (sentence case)	white (R)	160/32
	or		
Language, option B	If using one language only for the name of the locality:		
	'[locality]' (sentence case)	white (R)	160/32
	Language option A or B beside,		
	'an arrow (type D) aligned appropriately' beside the list of localities	white (R)	shaft 68 mm
	(repeat above as needed if multiple localities)		

Ref: clause 2.4(5)(ttt)

A13-3 Intersection direction – arrow board two directions Advises road users the direction to follow at an intersection to reach localities described.

Shape and size

rectangle with a pointed end (isosceles triangle, base the height of the rectangle, height approximately 40% of base) at each end pointing in the direction of the localities length sized to suit message x 700 mm height

Background green (R) or blue (R)

Border white (R) 25 mm

Border	white (R) 25 mm		
Legend	Description	Colour	Size
	Optional, A20-S11 (emergency medical services), above or beside the locality names	As for A20- S11	As for A20-S11
	Optional, A20-S18 (airfield), above or beside the locality names	As for A20- S18	As for A20-S18
	Optional, an A16 series route indicator symbol may be included beside or above the list of localities	As for A16	As for A16
	Two localities separated by a gap of 500 mm, with each locality consisting of		
Language, option A	If using both te reo Māori and English names for the locality:		
	'[te reo Māori name of locality]' (sentence case), above	yellow (R)	160/32
	'[English name of locality]' (sentence case)	white (R)	160/32
	or		
Language, option B	If using one language only for the name of the locality:		
	'[locality]' (sentence case),	white (R)	160/32
	Language option A or B beside,		
	A chevron parallel to, and located at, each pointed end of the sign	white (R)	chevron 350 mm high, stripe width 130 mm

Ref: clause 2.4(5)(uuu)

A15-1 Confirmation direction

Located beyond an intersection to reassure road users they are travelling toward the correct destination.

Shape and

rectangle sized to suit message

size

Background green (R) or blue (R)

Border white (R) 40 mm

Legend	Description	Colour	Size
	Optional, A20-S11 (emergency medical services), above or beside the locality names	As for A20- S11	As for A20-S11
	Optional, an A16 series route indicator symbol, above all locality names or beside the name of each locality	As for A20- S18	As for A20-S18
	Optional, an A16 series route indicator symbol above the localities or beside each locality if more than one route indicator symbol is applicable	As for A16	As for A16
Language, option A	If using both te reo Māori and English names for the locality:		
	'[te reo Māori name of locality]' (sentence case), above	yellow (R)	120/24
	'[English name of locality]' (sentence case)	white (R)	120/24
Language, option B	If using one language only for the name of the locality:		
	'[locality]' (sentence case)	white (R)	160/32
	Language option A or B beside,		
	'[distance] km' beside each locality	white (R)	120/24
	(repeat above as needed if multiple localities)		numerals Tpt Med 'x' =80 letters

Notes: sign normally contains no more than 3 localities and distances.

Ref: clause 2.4(5)(vvv)

A17-1 Place name

Indicates to the road user the place reached.

Shape and

rectangle length to suit message x 375 mm height

size

Background	green (R) or blue (R)		
Border	white (R) 40 mm		
Legend	Description	Colour	Size
Language, option A	If using both te reo Māori and English names for the locality:		
	'[te reo Māori name of locality]' (sentence case), above	yellow (R)	120/24 urban 160/32 rural
	'[English name of locality]' (sentence case)	white (R)	120/24 urban 160/32 rural
	or		
Language, option B	If using one language only for the name of the locality:		
	'[locality]' (sentence case)	white (R)	120/24 urban 160/32 rural

Ref: clause 2.4(5)(www)

A40-7	Shared zone
The roadway h	wond the sign is within a shared zone for the nurnoses

The roadway beyond the sign is within a shared zone for the purposes of clause 10.2 of the Land Transport (Road User) Rule 2004.

Shape and size	rectangle 600 x 1050 mm		
Background	blue (R)		
Border	white (R) 25 mm		
Legend	Description	Colour	Size
	"symbol of two children" beside	white (R)	160 x 135
	"symbol of pedestrian" both above	white (R)	90 x 150
	"symbol of cycle" beside	white (R)	160 x 100
	"symbol of car" both above	white (R)	120 x 100
	"ARA"	white (R)	100/15.5
	"WĀTEA"	white (R)	100/15.5
	"SHARED"	white (R)	100/14
	"ZONE"	white (R)	100/14

Ref: clause 2.4(5)(xxx)

A41-1 Motorway

Advises road users they are on a motorway and rules applying to motorway use apply. The sign may also be used on an on-ramp to a motorway to indicate the motorway begins.

Note: A41-1 series motorway signs may include the name of the motorway. Vertical dimensions of the signs must be increased by the amount required to fit the name above the word 'MOTORWAY'

Shape and size	rectangle	1800 x	600 mm
----------------	-----------	--------	--------

Background green (R)

Border white (R) 30 mm

Legend	Description	Colour	Size
	'TE ARA WHĀNUI''	white (R)	150/23
	'MOTORWAY'	white (R)	150/21

Ref: clause 2.4(5)(yyy)

A41-1.1 Motorway begins

Advises road users they are about to enter a motorway and rules applying to motorway use apply.

Background green (R)

Border white (R) 40 mm

Legend	Description	Colour	Size
	'KUA TĪMATA'	white (R)	250/43
	'TE ARA'	white (R)	250/43
	'WHĀNUI'	white (R)	250/43
	'MOTORWAY'	white (R)	250/39
	'BEGINS'	white (R)	250/39

Ref: clause 2.4(5)(zzz)

A41-1.2 Motorway ends advance information

Advises road users the motorway ends in the specified distance.

Shape and size rectangle 2700 x 2200 mm

Background green (R)

Border white (R) 40 mm

Legend	Description	Colour	Size
	'TE ARA'	white (R)	250/43
	'WHĀNUI KA'	white (R)	250/43

'MUTU [distance] m'	white (R)	numerals 250/39,
		'm' 150/23
'MOTORWAY'	white (R)	250/39
'ENDS [distance] m'	white (R)	numerals 250/39,
		'm' 150/23

		Ref:	clause 2.4(5)(aaaa)	
A41-1.3	Motorway ends			
Advises road users the motorway has ended and all normal road rules apply.				
Option A	erected at the point where the motorway ends			
Shape and size	rectangle 2550 x 2200 mm			
Background	green (R)			
Border	white (R) 40 mm			
Legend	Description	Colour	Size	
	'KUA MUTU'	white (R)	250/43	
	'TE ARA '	white (R)	250/43	
	'WHĀNUI'	white (R)	250/43	
	'MOTORWAY'	white (R)	250/39	
	'ENDS	white (R)	250/39	
Option B	erected on an off-ramp from	the motorway where the motor	orway ends	
Shape and size	rectangle 900 x 900 mm			
Background	green (R)			
Border	white (R) 25 mm			
Legend	Description	Colour	Size	
	'KUA MUTU'	white (R)	100/15.5	
	'TE ARA'	white (R)	100/15.5	
	'WHĀNUI'	white (R)	100/15.5	
	'MOTORWAY'	white (R)	100/14	
	'ENDS	white (R)	100/14	

Ref: clause 2.4(5)(bbbb)

A41-2 Expressway

Advises road users they are on a road often with similar characteristics to, but that is not, a motorway. It may have special conditions applying to its use and these should be clearly signed. The sign may also be used on an on-ramp to an expressway to indicate the expressway begins.

Note: A41-2 series expressway signs may include the name of the expressway. Vertical dimensions of the signs must be increased by the amount required to fit the name above the word 'EXPRESSWAY'.

3

Ref: clause 2.4(5)(cccc)

			Ref: clause 2.4(3)(cccc)
A41-2.1	Expressway begins		
Advises road user	s they are about to enter an exp	ressway.	
Shape and size	rectangle 2850 x 2200 mm		
Background	green (R) or blue (R)		
Border	white (R) 40 mm		
Legend	Description	Colour	Size
	'KUA TĪMATA'	white (R)	250/43
	'TE ARA'	white (R)	250/43
	'PUAKI'	white (R)	250/43
	'EXPRESSWAY'	white (R)	250/39
	'BEGINS'	white (R)	250/39

			Ref: clause 2.4(5)(dddd)	
A41-2.2	Expressway ends advance information			
Advises road users expressway ends in the specified distance				
Shape and size	rectangle 2700 x 2200 mm			
Background	green (R) or blue (R)			
Border	white (R) 40mm	white (R) 40mm		
Legend	Description	Colour	Size	
	'TE ARA'	white (R)	250/43	
	'PUAKI KA'	white (R)	250/43	
	'MUTU [distance] m'	white (R)	letters and numerals 250/43	
			'm' 150/23	

'EXPRESSWAY'	white (R)	250/39
'ENDS [distance] m'	white (R)	letters and numerals 250/39 'm' 150/23

			250/39 'm' 150/23
			Ref: clause 2.4(5)(eeee
A41-2.3	Expressway ends		
Advises road user	rs the expressway has ended. Tw	o options.	
Option A	erected at the point where the	e expressway ends	
Shape and size	rectangle 2550 x 2200 mm		
Background	green (R) or blue (R)		
Border	white (R) 40 mm		
Legend	Description	Colour	Size
	'KUA MUTU'	white (R)	250/43
	'TE ARA'	white (R)	250/43
	'PUAKI'	white (R)	250/43
	'EXPRESSWAY'	white (R)	250/39
	'ENDS'	white (R)	250/39
Option B	erected on an off-ramp from	the expressway where the	he expressway ends
Shape and size	rectangle 990 x 900 mm		
Background	green (R) or blue (R)		
Border	white (R) 25 mm		
Legend	Description	Colour	Size
	'KUA MUTU'	white (R)	100/15.5
	'TE ARA'	white (R)	100/15.5
	'PUAKI'	white (R)	100/15.5
	'EXPRESSWAY'	white (R)	100/14
	'ENDS'	white (R)	100/14

Ref: clause 2.4(5)(ffff)

A51-1	Cycle route advance direction – pr		2. 1(3)(1111)
Advises cyclists the direction to follow at the intersection ahead to reach named destinations.			
Shape and size	rectangle at least 600 x 450 mm and large enough to accommodate the message, in two panels: top panel 150 mm high, lower panel at least 300 mm high.		
Background	top panel blue (R), lower panel white	e (R)	
Border	blue (R) 20 mm		
Legend	Description	Colour	Size
Top panel	"cycle symbol" centralised in panel	white (R)	130 x 85 mm
	and optional symbol associated with the locality or the route	As for the symbol	100 x 100 mm maximum
Lower panel	Optional "[Route name]" (sentence case), above	white (R) text on a black background	Text: Tpt Med 'x' height 20 mm background: width to suit main legend x 60 mm high
Language, option A	If using both te reo Māori and English names for the same destination:		
	"[te reo Māori name of primary route destination]" (sentence case), above	black	Text: Tpt Med 'x' height 43 mm
	"[English name of primary route destination]" (sentence case), beside 'arrow (type D) aligned appropriately'	blue (R), blue (R)	Text: Tpt Med 'x' height 43 mm, arrow shaft: 27 mm
	or		
Language, option B	If using one language only for the name of the destination:		
	"[Primary route destination]" (sentence case), beside 'arrow (type D) aligned appropriately'	blue (R), blue (R)	Text: Tpt Med 'x' height 43 mm, arrow shaft: 27 mm
Language, option	Language option A or B above,		
A	a horizontal line, above	blue (R)	10 mm
	If using both te reo Māori and English names for the same destination:		
	"[te reo Māori Alternate destination]" (sentence case), above	black	Text: Tpt Med 'x' height 43 mm

	"[English alternate destination]" (sentence case), beside 'arrows (type D) aligned appropriately'	blue (R), blue (R)	Text: Tpt Med 'x' height 43 mm, arrow shaft: 27
	(repeat above as needed if multiple alternative destinations)		mm
	or		
Language, option B	If using one language only for the name of the destination:		
	"[Alternate destination]" (sentence case) or "[Alternative destinations]" (sentence case), beside 'arrows (type D) aligned appropriately'	blue (R), blue (R)	Text: Tpt Med 'x' height 43 mm, arrow shaft: 27 mm

Ref: clause 2.4(5)(gggg)

A51-2	Cycle route advance direction ma	n – primary route

Advises cyclists the direction to follow at the intersection ahead to reach named destinations.			
Shape and size	rectangle sized to suit the message, in two panels: top panel 150 mm high, lower panel sized to accommodate the map		
Background	top panel blue (R), lower panel wh	ite (R)	
Border	blue (R) 20 mm		
Legend	Description	Colour	Size
Top panel	"cycle symbol" centralised in panel	white (R)	130 x 85 mm
	and optional symbol associated with the locality or the route	As for the symbol	100 x 100 mm maximum
Lower panel	"[Graphical representation of the intersection ahead, showing details as necessary to explain the	cycle route: blue (R)	50 mm
	path of the cycle route and directions to alternative destinations.]" The map may include "road name" or "road names" and/or "destination" or "destinations" (destination may	route and crnative The map may ame" or "road destination" or destination. If using both te reo Māori and English names for the same destination.	
	be in te reo Māori and English or one language only) and directional arrows (type D). When a te reo Māori word is	Te reo Māori name of destination: black	Tpt Med 'x' height 43 mm
	used it is placed above the relevant destination name. All words in sentence case.	English name of destination: blue (R)	Tpt Med 'x' height 43 mm
		If using one language only for the name of	

the destination:

destination name: blue (R)	Tpt Med 'x' height 43 mm
arrows: blue (R)	shaft width 27 mm
road names: black, roads: grey, other details: black	Tpt Med 'x' height 21.5 mm 80 mm (main roads) 65 mm (other roads) as appropriate for the detail

Ref: clause 2.4(5)(hhhh)

110 mm high,

stripe width 45

mm (1 line of

210 mm high, stripe width 85

text),

A51-3 Cycle route intersection direction – primary route

Advises exclists the direction to follow at an intersection and the distances to named

Advises cyclists the direction to follow at an intersection and the distances to named destinations.			
Shape and size	rectangle with pointed end (isosceles triangle, base the height of the rectangle, height approximately 40% of the base), length to suit message x 150 mm high (1 line of text) or 250 mm high (2 lines of text).		
Background	blue (R) rectangle at least 160 mm wide x the height of the sign for the cycle symbol and optional symbol associated with the locality or route; white (R) for destination and chevron		
Border	blue (R) 10 mm		
Legend	Description	Colour	Size
	"Cycle symbol" (on blue background at square end of sign)	white (R)	130 x 85 mm
	and optional symbol associated with the locality or route (on blue background at square end of sign), beside	as for the symbol	100 x 100 mm maximum
Language, option A	If using both Māori and English names for the same destination:		
	"[te reo Māori destination name]" (sentence case), above	black	Tpt Med 'x' height 43 mm
	"[English destination name]" (sentence case),	blue (R)	Tpt Med 'x' height 43 mm
	beside,		
	"[distance] km" or "[distance] m", beside	blue (R)	Tpt Med 'x' height 43 mm

A chevron pointing in the direction blue (R)

of the destination, parallel to and

located at the pointed end of the

sign

			mm (2 lines of text)
	(repeat above as needed if multiple destinations, limited to 1 or 2 lines of text)		
	or		
Language, option B	If using one language only for the name of the destination:		
	"[Destination]" (sentence case) or "[Destinations]" (sentence case) (limited to 1 or 2 lines of text),	blue (R)	Tpt Med 'x' height 43 mm
	beside		
	"[distance] km" or "[distance] m", beside	blue (R)	Tpt Med 'x' height 43 mm
	A chevron pointing in the direction of the destination, parallel to and located at the pointed end of the sign	blue (R)	110 mm high, stripe width 45 mm (1 line of text), 210 mm high, stripe width 85 mm (2 lines of text)

Ref: clause 2.4(5)(iiii)

A51-4	Cycle route intersection direction arrow – local rout	40
A31-4	Cycle route intersection direction arrow – local rout	æ

Advises cyclists the direction to follow at an intersection and the distance to a named destination and the services available at the destination.

destination and the services available at the destination.			
Shape and size	rectangle length to suit the message x 200 mm high, in two panels: panel 1 at least 200 mm wide, panel 2 sized to accommodate the message		
Background	panel 1 blue (R), panel 2 white (R)		
Border	blue (R) 10 mm		
Legend	Description	Colour	Size
Panel 1	"Cycle symbol"	white (R)	130 x 85 mm
(closest to mounting post)	and optional symbol associated with the locality or route, beside	as for the symbol	100 x 100 mm maximum
Panel 2, Option A	1 destination and service symbols		
	If using both te reo Māori and English names for the same destination:		
Language, option A	"[te reo Māori destination name]" (sentence case), above	black	Tpt Med 'x' height 43 mm
	"[English destination name]" (sentence case), above	blue (R)	Tpt Med 'x' height 43 mm
or			

Language, option B	If using one language only for the name of the destination:		
	"[Destination]" (sentence case),	blue (R)	Tpt Med 'x' height 43 mm
	Language option A or B, beside		
	"[distance] km" or "[distance] m",	blue (R)	Tpt Med 'x' height 43 mm
	above		
	Up to 6 "A20-S symbols" or "A30-S symbols or "A51-S symbols", beside	white (R) symbol on blue (R) background	each symbol, including a border, maximised to fit an area 45 x 45 mm
	'arrow (type D) aligned appropriately'	blue (R)	shaft width 27 mm
Panel 2, Option B	2 destinations		
Language, option A	If using both te reo Māori and English names for the same destination:		
	"[te reo Māori destination 1 name]" (sentence case), above	black	Tpt Med 'x' height 43 mm
	"[English destination 1 name]" (sentence case),	blue (R)	Tpt Med 'x' height 43 mm
	or		
Language, option B	If using one language only for the name of the destination:		
	"[Destination 1]" (sentence case)	blue (R)	Tpt Med 'x' height 43 mm
	Language option A or B, beside		
	"[distance] km" or "[distance] m", above	blue (R)	Tpt Med 'x' height 43 mm
	'arrow (type D) aligned appropriately'	blue (R)	shaft width 27 mm
Language, option A	If using both te reo Māori and English names for the same destination:		
	"[te reo Māori destination 2 name]" (sentence case), above	black	Tpt Med 'x' height 32 mm
	"[English destination 2 name]" (sentence case)	blue (R)	Tpt Med 'x' height 32 mm
	or		
Language, option B	If using one language only for the name of the destination:		

"[Destination 2]" (sentence case),	blue (R)	Tpt Med 'x' height 32 mm
Language option A or B, beside		
"[distance] km" or "[distance] m", beside	blue (R)	Tpt Med 'x' height 32 mm
'arrow (type D) aligned appropriately'	blue (R)	shaft width 27 mm

			Ref: clause 2.4(5)(jjjj)
A51-5	Cycle route direction – primary ro	oute	
Advises cyclists the	e direction to follow to reach named d	estinations.	
Shape and size	rectangle at least 600 x 300 mm and large enough to accommodate the message, in two panels: top panel 150 mm high, lower panel at least 150 mm high.		
Background	top panel blue (R), lower panel white (R)		
Border	blue (R) 20 mm		
Legend	Description	Colour	Size
Top panel	"cycle symbol" centralised in panel	white (R)	130 x 85 mm
	and optional symbol associated with the locality or the route	as for the symbol	100 x 100 mm maximum
Lower panel			
Language, option A	If using both te reo Māori and English names for the same destination:		
	"[te reo Māori destination name]" (sentence case), above	black	Text: Tpt Med 'x' height 43 mm,
	"[English destination name]" (sentence case)	blue (R)	Text: Tpt Med 'x' height 43 mm,
	(repeat above as needed if multiple destinations)		
	or		
Language, option B	If using one language only for the name of the destination:		
	"[Destination]" (sentence case) or "[Destinations]" (sentence case),	blue (R)	Text: Tpt Med 'x' height 43 mm,
	Language option A or B, beside		

'arrows (type D) aligned arrows: blue shaft width 27 mi appropriately' (R)
--

		Re	f: clause 2.4(5)(kkkk)		
A51-8	Cycle route confirmation direction – primary route				
Confirms the route	Confirms the route that cyclists are on and advises the distances to the named destinations.				
Shape and size	rectangle at least 600 x 300 mm and large enough to accommodate the message, in two panels: top panel 150 mm high, lower panel at least 150 mm high.				
Background	top panel blue (R), lower panel white (R)				
Border	blue (R) 20 mm				
Legend	Description	Colour	Size		
Top panel	"cycle symbol" centralised in panel	white (R)	130 x 85 mm		
	and optional symbol associated with the locality or the route	as for the symbol	100 x 100 mm maximum		
Lower Panel	Optional "[Route name]" (sentence case), above	white (R) text on a black background	Text: Tpt Med 'x' height 20 mm background: width to suit main legend x 60 mm high		
Language, option A	If using both te reo Māori and English names for the same destination:				
	"[te reo Māori destination name]" (sentence case), above	black	Tpt Med 'x' height 43 mm		
	"[English destination name]" (sentence case),	blue (R)	Tpt Med 'x' height 43 mm		
	beside,				
	"[distance] km" or "[distance] m"	blue (R)	Tpt Med 'x' height 43 mm		
	(repeat above as needed if multiple destinations)				
Language, option B	If using one language only for the name of the destination:				
	"[Destination]" (sentence case) or "[Destinations]" (sentence case),	blue (R)	Tpt Med 'x' height 43 mm		
	beside				
	"[distance] km" or "[distance] m"	blue (R)	Tpt Med 'x' height 43 mm		

Part 2
New items inserted in Schedule 1 of Land Transport Rule: Traffic Control
Devices 2004

Ref: clause 2.3(6)

R1-8.4 Emergency speed limit

Highest speed limit is the number of km/h shown on the sign. Sign combination only used for emergency speed limits as defined by the Land Transport Rule: Setting of Speed Limits 2022.

Shape and size R1-1, 600 mm diameter sign (background, border and legend as for R1-1)

above a 'Emergency' supplementary sign

'Emergency' supplementary sign

Shape and size rectangle 1050 x 450 mm

Background orange (RF)
Border black 25 mm

Legend Description Colour Size

'Ohotata' black Text: Tpt Med 'x'

height 86 mm

'EMERGENCY' black 120/16.8

The speed limit is 60 km/h except when pedestrians are present then speed limit is 30km/h.

Shape and size rectangle backing board 1770 x 800 mm

Background white(R); two panels - standard speed limit top panel, bottom panel speed

limit when pedestrians present, separated by 20 mm line red

Border red 30 mm

Legend **Description** Colour Size Top panel R1-1, 60km/h speed white (R), as for R1-1 (600 mm diameter) **ABOVE** red (R) and black **Lower Panel** Symbol of children facing right, black 180 x 212 mm left of as for R1-1 (400 R1-1, 30km/h speed, centred, white (R), mm diameter) red (R) and black left of, Symbol of pedestrian facing left black 242 x 137 mm **ABOVE**

Supplementary beach sign (on same backing board):

Shape and size	rectangle 800 x 400 mm		
Background	yellow (R)		
Border	20 mm		
Legend	Description	Colour	Size
	'TĀTAHI'	black	100/17
	'BEACH'	black	100/15.5

R1-9.2 Riverbed variable speed limit

The speed limit is 60 km/h except when pedestrians are present then speed limit is 30km/h.

Shape and size rectangle backing board 1970 x 800 mm

Background white(R); two panels - standard speed limit top panel, bottom panel speed

limit when pedestrians present, separated by 20 mm line red

Border red 30 mm

Doruci	100 50 111111		
Legend	Description	Colour	Size
Top panel	R1-1, 60km/h speed ABOVE	White (R), red (R) and black	As for R1-1 (600 mm diameter)
Lower Panel	Symbol of children facing right, left of	black	180 x 212 mm
	R1-1, 30km/h speed, centred,	White (R), red (R) and black	As for R1-1 (400 mm diameter)
	left of Symbol of pedestrian facing left ABOVE	black	242 x 137 mm

Supplementary riverbed sign (on same backing board):

Shape and size rectangle 800 x 600 mm

Background yellow (R) **Border** 20 mm

Legend	Description	Colour	Size
	'PAPA'	black	100/17
	'WAI AWA'	black	100/17
	'RIVERBED'	black	100/15.5

A11-4.1 Advance direction – map - overhead

Advises road users lanes available to use at an interchange ahead to reach the localities described and the distance to the interchange. The line or lines for each lane are erected directly over the lane to which they refer.

Shape and

rectangle sized to suit message

size

Background green (R) or blue (R)

Border white (R) 50 mm

201401	, into (10) 00 inin		
Legend	Description	Colour	Size
	Optional, A20-S11 (emergency medical services), above or beside the locality names	As for A20- S11	As for A20-S11
	Optional, A20-S18 (airfield), above or beside the locality names	As for A20- S18	As for A20-S18
	Optional, an A16 series route indicator symbol, above or beside all locality names for a given direction on the map	As for A16	As for A16
	A symbolic diagram of the approach to the interchange depicted by lines which include a pointed end, and	white (R)	100 mm width line 100 mm shaft arrow
Language, option A	If using both te reo Māori and English names for the locality:		
	'[te reo Māori name of locality]' (sentence case), above	yellow (R)	240/48
	'[English name of locality]' (sentence case)	white (R)	240/48
	or		
Language, option B	If using one language only for the name of the locality:		
	'[locality]' (sentence case)	white (R)	240/48
	(repeat above as needed if multiple localities)		

Notes: multiple locality names may be positioned relative to the diagram. A distance may be positioned relative to the diagram.

A12-4 Exit number supplementary

Advises road users the reference number of the exit to which a sign refers.

Shape and

rectangle 430 mm high with width sized to suit the sign being supplemented

size

Background green (R) or blue (R) to match the sign being supplemented

Border white (R) 40 mm

Legend	Description	Colour	Size
	'PUTANGA', above	yellow (R)	100/15.5
	'EXIT', beside	white (R)	100/15.5
	'[the exit reference or number]'	white (R)	150/23